

Würth Elektronik eiSos GmbH &amp; Co. KG

EMC &amp; Inductive Solutions

Max-Eyth-Straße 1 · 74638 Waldenburg · Germany

Tel. +49 (0) 79 42 945-0 · Fax +49 (0) 79 42 945-400

eiSos@we-online.de · www.we-online.de



## Product / Process Change Notification (PCN)

- Major change  
 Minor change

**PCN #:** PCN\_FeSAFB\_20220504

**Affected Series:** WE-SAFB; 7427002, 74270010, 74270011, 74270012

**PCN Date:** February 04, 2022

**Effective Date:** May 04, 2022

### Change Category:

- Equipment / Location  
 General Data  
 Material  
 Process  
 Product Design  
 Shipping / Packaging  
 Supplier  
 Software

**Contact:** Product Management

**Phone:** +49 (0) 7942 - 945 5001

**Fax:** +49 (0) 7942 - 945 5179

**E-Mail:** pcn.eisos@we-online.com

### Data Sheet Change:

- Yes  No

### Attachment:

- Yes  No

### DESCRIPTION AND PURPOSE OF CHANGE:

To increase the production capability of the following WE-SAFB part numbers, Würth Elektronik has implemented an additional production line.

All products with date code 2022-03-01 or later, can be affected by this change.

There will be no change in form, fit, function, quality or reliability of the product.

### DETAIL OF CHANGE:

Neither electrical specification values at 25MHz or 100MHz nor mechanical properties of the parts will be changed.

The production lines can be identified by the first three digits of the lot number **XXX** XX XX XXXX XXX.

Affected Part numbers	Lot number of already established production line:	Lot number of additional production line:
7427002, 74270010, 74270011, 74270012	Lot number starting with 240 Country of Origin: China	Lot number starting with 241 Country of Origin: Taiwan

### RELIABILITY / QUALIFICATION SUMMARY:

Product approval is according to the specification criteria and is internally released by the Product Management Department.

#### The following items are part of the internal release process:

- Visual Appearance (Surface, Burr, Contaminations, ...)
- Mechanical Parameters (according as specified in the Datasheet)
- Electrical Parameters (according 25MHz and 100MHz as specified in the Datasheet)
- Approval of production line