

PCN Number: SC141602

Notification Date*: May 6, 2014

Title: EOL and Replacement of the AT30TS75 Digital Temperature Sensor with the New AT30TS74 and AT30TS75A				
Product Identification: All versions of the AT30TS75				
Reason for Change:	<input type="checkbox"/> Material / Composition	<input type="checkbox"/> Manufacturing Location		
	<input type="checkbox"/> Processing / Manufacturing	<input type="checkbox"/> Quality / Reliability		
	<input checked="" type="checkbox"/> Design / Firmware	<input type="checkbox"/> Logistics		
	<input checked="" type="checkbox"/> Datasheet	<input type="checkbox"/> Other:		
Change Description: The AT30TS75 Digital Temperature Sensor is being replaced by two new Digital Temperature Sensors (AT30TS74 and AT30TS75A) to address some of the errata specifications listed in the AT30TS75 datasheet and to better address end market/application requirements. In addition, both the AT30TS74 and AT30TS75A have been improved over the AT30TS75 to feature an industry-first, wide supply voltage range of 1.7V to 5.5V versus the previous 2.7V to 5.5V of the AT30TS75. Lastly, the introduction of the AT30TS74 enables the ability to offer a new WLCSP (wafer-level chip scale package) to address space-constrained applications and to allow placement of the Temperature Sensor as close as possible to desired "hot spot" measurement points. Attachment A highlights the differences between the AT30TS75 and the new, replacement AT30TS74 and AT30TS75A devices.				
Identification Method to Distinguish Change: The base catalog part number changes from AT30TS75 to either AT30TS74 or AT30TS75A. Table 1 lists the full catalog part number combinations for each package option. Please refer to the AT30TS75, AT30TS74, and AT30TS75A datasheets for details on the part marking schemes for each package type.				
Table 1				
EOL Part Number	Replacement Part Number (Option 1)	Replacement Part Number (Option 2)	Package	Carrier Type
AT30TS75-MA8-T	AT30TS74-MA8M-T	AT30TS75A-MA8M-T	UDFN	T&R
AT30TS75-SS8-B	AT30TS74-SS8M-B	AT30TS75A-SS8M-B	SOIC	Bulk
AT30TS75-SS8-T	AT30TS74-SS8M-T	AT30TS75A-SS8M-T	SOIC	T&R
AT30TS75-XM8-B	AT30TS74-XM8M-B	AT30TS75A-XM8M-B	MSOP	Bulk
AT30TS75-XM8-T	AT30TS74-XM8M-T	AT30TS75A-XM8M-T	MSOP	T&R
<i>Note: Standard datasheet offerings are listed in the table; however, this PCN also applies to all special CAN (customer specific) part numbers that are not listed in the table.</i>				
Qualification Data:	<input checked="" type="checkbox"/> Available	<input type="checkbox"/> Will be available (mm/dd/yr):	<input type="checkbox"/> Not Applicable	

Samples:	<input checked="" type="checkbox"/> AT30TS75A Available	<input checked="" type="checkbox"/> AT30TS74 Will be available (mm/dd/yr): SOIC/MSOP on 5/12/14 UDFN on 6/9/14	<input type="checkbox"/> Not Applicable
-----------------	---	--	---

Quantifiable Impact on Quality & Reliability:

None

Forecasted Availability Date: Now**Last Time Buy Date:** July 15, 2014**Last Ship Date:** December 31, 2014**All orders placed after the notification date are non-cancellable and non-returnable (NCNR).***Atmel Contact:** Please contact your Atmel Sales Representative or Distributor for additional information (when replying via e-mail please include the PCN number in subject line).

Information provided herein is in connection with Atmel products and this information is provided "AS IS". Atmel assumes no responsibility for any errors that may appear in this document. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Atmel's Terms and Conditions of Sale for such products, Atmel assumes no liability whatsoever, and Atmel disclaims any express or implied warranty, including liability or warranties relating to fitness for a particular purpose, merchantability, or non-infringement of any patent, copyright or other intellectual property right. Atmel products are not intended for use in a product or system intended to support or sustain life which, if it fails, can be reasonably expected to result in significant personal injury. Atmel may make changes to specifications and product descriptions at any time, without notice.

Attention Distributors: Product(s) identified in this notification will become obsolete and as such this EOL notification will act as the official written notification. All obsolete products will be listed in the next published quarterly distributor price book, following an PCN/EOL change, and listed on the obsolescence form which accompanies said price book. Within thirty (30) days from the published date of the price book, Distributor shall notify Atmel in writing of Distributor's then current inventory of the obsolete product

CUSTOMER ACKNOWLEDGEMENT OF RECEIPT: Atmel requests you acknowledge receipt of this PCN / EOL. Please complete and email to pcnadm@atmel.com and the Atmel Contact listed above. In your acknowledgement, you can grant approval or request additional information. **Atmel will deem this change accepted unless specific conditions of acceptance are provided in writing within 30 days from the date of this notice.**

To be completed by customer: Approved Rejected (Please state reason for rejection):

Company:

Name:

Title:

Date:

Email

Address:

Location:

Comments:

Attachment A

RED text indicates changes/improvements

Parameter/Feature	AT30TS75 (based on 09/2013 datasheet)		AT30TS74 (based on 03/2014 datasheet)		AT30TS75A (based on 03/2014 datasheet)	
Operating Voltage	2.7V to 5.5V		1.7V to 5.5V		1.7V to 5.5V	
Operating Temperature	-55°C to +125°C		-55°C to +125°C		-55°C to +125°C	
Temperature Sensor Accuracy and Conversion Characteristics						
Temperature Sensor Accuracy	±1.0°C typ (±1.5°C max)	T _A = 0°C to +55°C V _{CC} = 2.7V to 3.6V	±1.0°C typ (±2.0°C max)	T _A = -20°C to +100°C V _{CC} = 1.7V to 5.5V	±0.5°C typ (±1.0°C max)	T _A = 0°C to +85°C V _{CC} = 1.7V to 5.5V
	±1.0°C typ (±2.0°C max)	T _A = -5°C to +90°C V _{CC} = 2.7V to 3.6V	±2.0°C typ (±3.0°C max)	T _A = -40°C to +125°C V _{CC} = 1.7V to 5.5V	±1.0°C typ (±2.0°C max)	T _A = -25°C to +105°C V _{CC} = 1.7V to 5.5V
	±2.0°C typ (±3.0°C max)	T _A = -20°C to +125°C V _{CC} = 2.7V to 3.6V	±3.0°C typ	T _A = -55°C to +125°C V _{CC} = 1.7V to 5.5V	±2.0°C typ (±3.0°C max)	T _A = -40°C to +125°C V _{CC} = 1.7V to 5.5V
	±1.0°C typ (±2.0°C max)	T _A = 0°C to +55°C V _{CC} = 3.6V to 5.5V			±3.0°C typ	T _A = -55°C to +125°C V _{CC} = 1.7V to 5.5V
	±2.0°C typ (±3.0°C max)	T _A = -20°C to +105°C V _{CC} = 3.6V to 5.5V				
	±3.0°C typ	T _A = -40°C to +125°C V _{CC} = 2.7V to 5.5V				
	±3.0°C typ	T _A = -55°C to +125°C V _{CC} = 2.7V to 5.5V				
Conversion Resolution	Selectable 9 to 12 bits (0.5°C to 0.0625°C)		Selectable 9 to 12 bits (0.5°C to 0.0625°C)		Selectable 9 to 12 bits (0.5°C to 0.0625°C)	
Conversion Time	25ms typ (37.5ms max)	9-bit resolution	25ms typ (37.5ms max)	9-bit resolution	25ms typ (37.5ms max)	9-bit resolution
	50ms typ (75ms max)	10-bit resolution	50ms typ (75ms max)	10-bit resolution	50ms typ (75ms max)	10-bit resolution
	100ms typ (150ms max)	11-bit resolution	100ms typ (150ms max)	11-bit resolution	100ms typ (150ms max)	11-bit resolution
	200ms typ (300ms max)	12-bit resolution	200ms typ (300ms max)	12-bit resolution	200ms typ (300ms max)	12-bit resolution
Power-Up Conditions						
Power-On Reset Time (t _{POR})	500µs max		1ms max		1ms max	
Power-On Reset Voltage (V _{POR})	2.6V max		1.6V max		1.6V max	
Max Allowed Power-Up Time (t _{PU})	1ms max		N/A		N/A	

Attachment A (Continued)

RED text indicates changes/improvements

Parameter/Feature	AT30TS75 (based on 09/2013 datasheet)		AT30TS74 (based on 03/2014 datasheet)		AT30TS75A (based on 03/2014 datasheet)	
DC Characteristics						
Active Current, Bus Inactive, Active Temperature Conversions	95µA typ (125µA max)	$V_{CC} = 3.3V$	60µA typ (75µA max)	$1.7V \leq V_{CC} \leq 2.0V$	60µA typ (75µA max)	$1.7V \leq V_{CC} \leq 2.0V$
	120µA typ (175µA max)	$V_{CC} = \text{Max (5.5V)}$	65µA typ (95µA max)	$2.7V \leq V_{CC} \leq 3.6V$	65µA typ (95µA max)	$2.7V \leq V_{CC} \leq 3.6V$
			85µA typ (125µA max)	$4.5V \leq V_{CC} \leq 5.5V$	85µA typ (125µA max)	$4.5V \leq V_{CC} \leq 5.5V$
Active Current, Bus Active, $f_{SCL} = 400kHz$ Active Temperature Conversions	125µA typ (175µA max)	$V_{CC} = 3.3V$	120µA typ (160µA max)	$1.7V \leq V_{CC} \leq 2.0V$	120µA typ (160µA max)	$1.7V \leq V_{CC} \leq 2.0V$
	200µA typ (250µA max)	$V_{CC} = \text{Max (5.5V)}$	150µA typ (225µA max)	$2.7V \leq V_{CC} \leq 3.6V$	150µA typ (225µA max)	$2.7V \leq V_{CC} \leq 3.6V$
			225µA typ (325µA max)	$4.5V \leq V_{CC} \leq 5.5V$	225µA typ (325µA max)	$4.5V \leq V_{CC} \leq 5.5V$
Active Current, Bus Active, $f_{SCL} = 3.4MHz$ Active Temperature Conversions	350µA typ (650µA max)	$V_{CC} = 3.3V$	235µA typ (375µA max)	$2.2V \leq V_{CC} \leq 3.6V$	235µA typ (375µA max)	$2.2V \leq V_{CC} \leq 3.6V$
	400µA typ (750µA max)	$V_{CC} = \text{Max (5.5V)}$	610µA typ (800µA max)	$4.5V \leq V_{CC} \leq 5.5V$	610µA typ (800µA max)	$4.5V \leq V_{CC} \leq 5.5V$
Shutdown Mode Current, Bus Inactive	0.6µA typ (1.5µA max)	$V_{CC} = 3.3V$	0.4µA typ (2.5µA max)	$1.7V \leq V_{CC} \leq 2.0V$	0.4µA typ (2.5µA max)	$1.7V \leq V_{CC} \leq 2.0V$
	1.1µA typ (3.0µA max)	$V_{CC} = \text{Max (5.5V)}$	0.6µA typ (3.5µA max)	$2.7V \leq V_{CC} \leq 3.6V$	0.6µA typ (3.5µA max)	$2.7V \leq V_{CC} \leq 3.6V$
			1.2µA typ (5.5µA max)	$4.5V \leq V_{CC} \leq 5.5V$	1.2µA typ (5.5µA max)	$4.5V \leq V_{CC} \leq 5.5V$
Shutdown Mode Current, Bus Active, $f_{SCL} = 400kHz$	115µA typ (165µA max)	$V_{CC} = 3.3V$	110µA typ (140µA max)	$1.7V \leq V_{CC} \leq 2.0V$	110µA typ (140µA max)	$1.7V \leq V_{CC} \leq 2.0V$
	170µA typ (220µA max)	$V_{CC} = \text{Max (5.5V)}$	130µA typ (180µA max)	$2.7V \leq V_{CC} \leq 3.6V$	130µA typ (180µA max)	$2.7V \leq V_{CC} \leq 3.6V$
			180µA typ (270µA max)	$4.5V \leq V_{CC} \leq 5.5V$	180µA typ (270µA max)	$4.5V \leq V_{CC} \leq 5.5V$
Shutdown Mode Current, Bus Active, $f_{SCL} = 3.4MHz$	310µA typ (600µA max)	$V_{CC} = 3.3V$	210µA typ (365µA max)	$2.2V \leq V_{CC} \leq 3.6V$	210µA typ (365µA max)	$2.2V \leq V_{CC} \leq 3.6V$
	360µA typ (700µA max)	$V_{CC} = \text{Max (5.5V)}$	550µA typ (750µA max)	$4.5V \leq V_{CC} \leq 5.5V$	550µA typ (750µA max)	$4.5V \leq V_{CC} \leq 5.5V$
AC Characteristics						
Maximum Clock Frequencies	3.4MHz (High-Speed Mode)	$V_{CC} \geq 2.7V$	3.4MHz (High-Speed Mode)	$V_{CC} \geq 2.2V$	3.4MHz (High-Speed Mode)	$V_{CC} \geq 2.2V$
	400kHz (Fast Mode)	$V_{CC} \geq 2.7V$	1MHz (Fast Mode Plus)	$V_{CC} < 2.2V$	1MHz (Fast Mode Plus)	$V_{CC} < 2.2V$
Errata						
Errata 1	The internal fault counter will be reset when updating the Configuration Register, the T_{HIGH} Limit Register, or the T_{LOW} Limit Register			None	None	
Errata 2	Depending on power supply ramp time, the ALERT pin may not be configured in the proper state to be a true open drain			None	None	